



Wiser With Energy

Technical Data Sheet

V180210

FACADE5+protect



Liquisol bvba Noorderlaan 147 B9,2030 Antwerpen, België
btw: BE0648.867.048 tel: 00 32 32 56 01 72 verf@liquisol.com
In case of conflict: <http://ec.europa.eu/consumers/odr>



FACADE5+protect is based on 10% active materials: silanes, siloxanes and fluorinated carbon resins, which are dissolved in water. It reduces the infiltration of moisture into porous building materials, without causing any significant changes to its water vapour permeability. It also makes the surface water and oil repellent



Watch the “how to install” movie. Clean the surface with s00p RWC, Possibly in combination with a high pressure cleaner. After cleaning, the surface must be totally dry before installation.



FACADE5+protect is sold in 5 liter pouch zak with screwdop. Store between 4°C en 30°C , do not store into direct sunlight. Use before 6 months after opening and 1 year after purchase

EAN code 5 liter = 5425027113253

The usage for 5 liter = 10 to 40 m² or 107 to 430 sq
For the right evaluation, make use of the absorption test with a Karsten pipe.



Make use of personal protection gear. In case of spraying FACADE5+protect make use of : Mask, combination filter at least A/P2. Proper handgloves and working clothes. The EU limit for 4EVERblue is (Klasse A/i) : 2010: 140g/liter. VOC level is max 50g/ liter. Read the MSDS.



Authorized Liquisol Applicator ALA may give 5 years factory warranty on vertical walls. At correct installation, a lifetime of 8 to 10 year can be expected. Horizontal surfaces must be treated annually



Treatment involves atomization under low pressure. FACADE5+protect should be applied from bottom to top, using horizontal back-and-forth movements. Two treatments should be conducted wet-on-wet. You are advised to use a backpack sprayer or electric pump designed for this purpose, so that the product can be atomized on the surface under constant pressure. Avoid the formation of puddles.

FACADE5+protect can be applied to facades, bricks, natural stone, concrete, tiles, and on horizontal concrete surfaces, provided they are sufficiently porous. FACADE5+protect is not suitable for application on surfaces that have been covered with organic paints or synthetic coatings.



WTCB test rapport: D622 X 935/EXT N labo REN

Water absorption efficiency : klasse A +95%

Decrease of dryness : klasse A - 30%

Colour : klasse a - = 6

Glare difference : klasse a - = 3%

