



Wiser With Energy

Technical Data Sheet

V180227

INSUL8deco essential



Liquisol bvba Noorderlaan 147 B9,2030 Antwerp, Belgium
VAT: BE0648.867.048 tel: 00 32 32 56 01 72 verf@liquisol.com
In case of conflict: <http://ec.europa.eu/consumers/odr>



INSUL8deco essential is a thermal infra red reflective waterborn acryl coating. To be applied on interior walls an ceilings. Available in 15 heritage colours.

Visit the "how to install" movie. Clean the surface with s00p RWC.



INSUL8deco essential is delivered in a plastic pouchbag with screwdop. Store between 4°C and 30°C , do not store into direct sunlight. Use before 6 months after opening and 1 year after purchase
EAN code 5 liter = 5425027112553

The usage per liter is 8 m² or 86 sqf
5 liter pouchbag = 40 m² = 430 sqf



Make use of personal protection gear. In case of spraying INSUL8deco make use of : Mask, combinationfilter at least A/P2. Proper handgloves and working clothes. The EU limiet for INSUL8deco is (Klasse A/i) : 2010: 140g/ liter. VOC level is 5g/ liter. Read the MSDS.



Authorized Liquisol Applicator ALA may give 8 years factory warranty.
At at correct installation, a lifetime of 10 to 15 year can be expected.



Use paintroller or airmix with opening 018 – 021, pressure = 80 - 150 bar (Graco Airmix 595.)

apply at min 5°C , relative humidity = max 80% Surface temperature = min 5°C- max 35°C. dry = 4h at 20°C and 65% RH (relatieve humidity)

